

## Vibration Detector

### LS-848-2



## Vibration Detector

### Description

This digital vibration detector LS-848-2 use the international advanced photoelectric sensor elements which with CPU processing technology to ensure the rigorous monitoring for the protective coverage. Users can adjust its Detective Sensitivity to balance point correctly. It is applicable for ATM (Automatic Teller Machine), banks, insurance company, Finance Office, especially safety box, etc. It can detect any action of knock, destruction and big movements.

### Technical Specifications

Product Category	LS-848-2
Operating Voltage	DC12V (adapt 9~16Vdc)
Standby Current	11mA (at 12VDC)
Alarm Contact	0.1A, 24V, NC
Tamper Contact	0.1A, 24V, NC
Alarm Time	2.2 Second minimum
Initialization Time	<2 minutes
Sensor	Intelligent Sensor
Operating Radius	3m
Working Temperature	-20 degree to +50 degree
Storage Temperature	-20 degree to +60 degree
Mounting	Surface
Size	85 x 26 x 25mm

### Diagram

#### Wire Connection

Alarm: NC Dry Contact

Tamper: NC Dry Contact

12V+: 12VDC

12-: GND

### Manufacturer

Shenzhen Longsin Intelligence Technology CO., Ltd

Address: Block B, Kaijieda Industrial Zone, Huachang Road, Dalang, Longhua Town, Baoan District, Shenzhen, China

Website: [www.longsin.cn](http://www.longsin.cn)

